D 263[®] LA[§] Thin Glass

Product Information

D 263[®] LA eco thin glass (LA = low alpha) is a colorless borosilicate glass. It is the only low-alpha radiation sheet glass available in the market today and is produced by a SCHOTT specific down-draw method.

Using the purest raw materials and select tank materials ensure the very low alpha radiation for D 263[®] LA eco thin glass.

It is available in sheet form in different thicknesses between 0.145 mm and 1.3 mm.

D 263[®] LA eco thin glass is manufactured with eco-friendly refining agents.

Applications


Packaging of radiation-sensitive sensors such as e.g. CCD image sensors.

Features

• Low alpha radiation

_

- High luminous transmittance
- Coefficient of thermal expansion matching to ceramic
- Low surface roughness due to firepolished surface
- Sheet glass sizes enable flexible wafer sizes
- Tight thickness control
- Easy to cut using the scribe and break method



Technical Data	
Dimensions	Square and round custom sizes
Thicknesses	between 0.145 mm and 1.3 mm
Luminous transmittance τ_{vD6S} (d = 1.1 mm)	91.7%
Coefficient of mean linear thermal expansion α (20 °C; 300 °C) (static measurement)	7.2 x 10 ⁻⁶ K ⁻¹
Transformation temperature Tg	557 °C
Dielectric constant ε_r at 1 MHz	6.7
Refractive index n _D	1.5230
Density ρ (annealed at 40 °C/h)	2.51 g/cm ³
Intensity of α -radiation	< 0.0030 counts (h x cm²)



SCHOTT AG Hattenbergstrasse 10 55122 Mainz Germany Phone +49 (0)6131/66-3572 info.special-glass-wafer@schott.com

www.schott.com/special-glass-wafer



