

## SF11 785258.474

$n_d = 1.78472$   
 $n_e = 1.79190$

$v_d = 25.76$   
 $v_e = 25.55$

$n_F - n_C = 0.030467$   
 $n_{F'} - n_{C'} = 0.030997$

### Refractive Indices

|              | $\lambda$ [nm] |         |
|--------------|----------------|---------|
| $n_{2325.4}$ | 2325.4         | 1.73294 |
| $n_{1970.1}$ | 1970.1         | 1.73843 |
| $n_{1529.6}$ | 1529.6         | 1.74506 |
| $n_{1060.0}$ | 1060.0         | 1.75445 |
| $n_t$        | 1014.0         | 1.75579 |
| $n_s$        | 852.1          | 1.76200 |
| $n_r$        | 706.5          | 1.77125 |
| $n_C$        | 656.3          | 1.77599 |
| $n_{C'}$     | 643.8          | 1.77734 |
| $n_{632.8}$  | 632.8          | 1.77862 |
| $n_D$        | 589.3          | 1.78446 |
| $n_d$        | 587.6          | 1.78472 |
| $n_e$        | 546.1          | 1.79190 |
| $n_F$        | 486.1          | 1.80645 |
| $n_{F'}$     | 480.0          | 1.80834 |
| $n_g$        | 435.8          | 1.82518 |
| $n_h$        | 404.7          | 1.84208 |
| $n_i$        | 365.0          |         |
| $n_{334.1}$  | 334.1          |         |
| $n_{312.6}$  | 312.6          |         |
| $n_{296.7}$  | 296.7          |         |
| $n_{280.4}$  | 280.4          |         |
| $n_{248.3}$  | 248.3          |         |

### Constants of Dispersion Formula

|       |              |
|-------|--------------|
| $B_1$ | 1.738484030  |
| $B_2$ | 0.311168974  |
| $B_3$ | 1.174908710  |
| $C_1$ | 0.013606860  |
| $C_2$ | 0.0615960463 |
| $C_3$ | 121.92271100 |

### Constants of Formula for $dn/dT$

|                                  |           |
|----------------------------------|-----------|
| $D_0$                            | 1.12E-05  |
| $D_1$                            | 1.81E-08  |
| $D_2$                            | -5.03E-11 |
| $E_0$                            | 1.46E-06  |
| $E_1$                            | 1.58E-09  |
| $\lambda_{TK}$ [ $\mu\text{m}$ ] | 0.282     |

### Temperature Coefficients of the Refractive Index

| [°C]    | $\Delta n_{rel}/\Delta T$ [ $10^{-6}/K$ ] |      |      | $\Delta n_{abs}/\Delta T$ [ $10^{-6}/K$ ] |      |      |
|---------|---|------|------|---|------|------|
|         | 1060.0                                    | e    | g    | 1060.0                                    | e    | g    |
| -40/-20 | 8.4                                       | 11.7 | 15.8 | 6.1                                       | 9.2  | 13.3 |
| +20/+40 | 9.2                                       | 12.9 | 17.6 | 7.7                                       | 11.3 | 16.0 |
| +60/+80 | 9.6                                       | 13.6 | 18.7 | 8.4                                       | 12.4 | 17.4 |

### Internal Transmittance $\tau_i$

| $\lambda$ [nm] | $\tau_i$ [10mm] | $\tau_i$ [25mm] |
|----------------|-----------------|-----------------|
| 2500           | 0.820           | 0.610           |
| 2325           | 0.870           | 0.700           |
| 1970           | 0.971           | 0.930           |
| 1530           | 0.993           | 0.982           |
| 1060           | 0.999           | 0.997           |
| 700            | 0.997           | 0.993           |
| 660            | 0.996           | 0.991           |
| 620            | 0.996           | 0.991           |
| 580            | 0.996           | 0.991           |
| 546            | 0.996           | 0.989           |
| 500            | 0.990           | 0.976           |
| 460            | 0.976           | 0.940           |
| 436            | 0.940           | 0.860           |
| 420            | 0.870           | 0.700           |
| 405            | 0.650           | 0.340           |
| 400            | 0.530           | 0.200           |
| 390            | 0.180           | 0.010           |
| 380            |                 |                 |
| 370            |                 |                 |
| 365            |                 |                 |
| 350            |                 |                 |
| 334            |                 |                 |
| 320            |                 |                 |
| 310            |                 |                 |
| 300            |                 |                 |
| 290            |                 |                 |
| 280            |                 |                 |
| 270            |                 |                 |
| 260            |                 |                 |
| 250            |                 |                 |

### Color Code

$\lambda_{80} / \lambda_5$  44/39

### Remarks

lead containing glass type

### Relative Partial Dispersion P

|           |        |
|-----------|--------|
| $P_{s,t}$ | 0.2039 |
| $P_{C,s}$ | 0.4590 |
| $P_{d,C}$ | 0.2866 |
| $P_{e,d}$ | 0.2356 |
| $P_{g,F}$ | 0.6147 |
| $P_{i,h}$ |        |

### Relative Partial Dispersion P'

|             |        |
|-------------|--------|
| $P'_{s,t}$  | 0.2004 |
| $P'_{C,s}$  | 0.4949 |
| $P'_{d,C'}$ | 0.2380 |
| $P'_{e,d}$  | 0.2316 |
| $P'_{g,F'}$ | 0.5433 |
| $P'_{i,h}$  |        |

### Deviation of Rel. Partial Disp.

#### $\Delta P$ from the normal line

|                  |         |
|------------------|---------|
| $\Delta P_{C,t}$ | -0.0043 |
| $\Delta P_{C,s}$ | -0.0040 |
| $\Delta P_{F,e}$ | 0.0029  |
| $\Delta P_{g,F}$ | 0.0142  |
| $\Delta P_{i,g}$ |         |

### Chemical Properties

|    |     |
|----|-----|
| CR | 1   |
| FR | 0   |
| SR | 1   |
| AR | 1.2 |
| PR | 1   |

### Other Properties

|   |       |
|---|-------|
| $\alpha_{-30/+70^\circ\text{C}}$ [ $10^{-6}/K$ ]  | 6.1   |
| $\alpha_{+20/+300^\circ\text{C}}$ [ $10^{-6}/K$ ] | 6.8   |
| $T_g$ [°C]  | 503   |
| $T_{10}^{13}$ [°C]                                | 500   |
| $T_{10}^{7.6}$ [°C]                               | 635   |
| $c_p$ [J/(g·K)]                                   | 0.431 |
| $\lambda$ [W/(m·K)]                               | 0.737 |
| $\rho$ [g/cm <sup>3</sup> ]                       | 4.74  |
| $E$ [ $10^3$ N/mm <sup>2</sup> ]                  | 66    |
| $\mu$   | 0.235 |
| $K$ [ $10^{-6}$ mm <sup>2</sup> /N]               | 1.33  |
| $HK_{0.1/20}$                                     | 450   |
| HG  | 1     |